



# FEATURES AND SPECIFICATIONS

- Au coating in air or argon
  - Maximum capacity: 6 samples
  - Average coating time: 6 minutes
  - Additional vacuum & drying modes
  - Low energy dual stage pump
- 
- Vacuum & drying modes 7 Pa to 150 Pa (continuously selectable)
  - Gold layer thickness 1 to 100 nm (continuously selectable)
  - Process time 1 to 600 minutes (continuously selectable)
  - Process chamber Borosilicate glass Ø 100 mm x 150 mm height
  - Implosion shield PET Ø 120 mm x 150 mm height
  - Vacuum connector DN 16 KF
  - Process gas connector 4 x 1 mm
  - Process gas supply Air or argon (0,6 bar)
  - Operating voltage 110 – 240 V AC, 50/60 Hz
  - Dimensions 340 x 340 x 290 (mm, W x D x H)
  - Weight 11 kg
  - Supplied accessories 1x gold target Ø 30 mm, thickness 100 µm (99,999% purity), international power plug set, printed user manual

## DUAL STAGE VACUUM PUMP

- Can be ordered separately as “pump kit” including
- Two-stage roughing-pump with a pump capacity of 4.8 m<sup>3</sup>/h
- Metal vacuum hose, DN 16 KF, length 1 m
- 2 x fittings and 2 x seals DN 16 KF
- 1 x oil mist filter

